



MODIFIED DRY DENSITY & MOISTURE CONTENT RELATION OF SOIL TEST REPORT

AS 1289.5.2.1

Client	Stass Environmental	Ticket No.	S2607
Client Address	PO Box 11, Kalamunda	Report No.	LLS18/5525_1_MMDD
Project	Material Assessment	Sample No.	LLS18/5525
Sampling Location	Waroona Pit	Date Received	-
Sample Identification	SE1	Date Tested	23/11/2018
Sampling Method	Sampled by Client, Tested as Received	Preparation Method	AS1289.1.1
Liquid Limit Method	Visual/tactile assessment by competent technician	Sample Curing Time	2 Hours

Override Material

Retained 19.0mm (%)	0
Retained 37.5mm (%)	0


AS 1289.5.2.1, 2.1.1, 1.1

Laboratory Moisture & Density Results

Moisture Content (%)	8.6	11.5	14.8	17.1
Dry Density (t/m ³)	1.676	1.700	1.721	1.712

Plot: Dry Density vs. Moisture Content

Dry Density (t/m³)



Modified Maximum Dry Density (t/m³) **1.72**

Modified Optimum Moisture Content (%) **15.0**

Comments:

The above air void lines are derived from a calculated apparent particle density of 2.555 t/m³



Accredited for compliance with ISO/IEC 17025 - Testing
Accreditation No. 19872

WORLD RECOGNISED ACCREDITATION This document may not be reproduced except in full.

Approved Signatory:

Name: Matt van Herk
Function: Laboratory Manager
Date: 27-November-2018